



# ARCTIC ARMOR™

## MACHINE FILM

Exceptional performance in extreme cold and dusty application environments

### Features & Benefits

- Maximizes overall load stability and containment with less film
- Great puncture and tear resistance
- Excellent performance consistency
- High, reliable one-sided cling
- Ideal film clarity for product scanning

### Ideal Load Types

- B and some C loads
- Down-gaugeable for A loads

### Equipment

- All equipment types, including rotary arm and high speed
- Recommended RPM: All
- Optimal pre-stretch range: 200%, up to 300% (thickness and application dependent)

### Wrapping Environments

- **Temperature:** Ideal for most cold, frozen, and dusty environments
- **Humidity:** High, medium, or low



### Ultra High Performance, Cast, Machine Film, Aggressive One-Sided Cling

Part No.	Product Code	Gauge (mil)	Microns	Width (in)	Length (ft)	Pounds per Roll	Rolls per Pallet
1757788	AAS1142010250	45	11.4	20	10,250	36.9	40
1757789	AAS1143010250	45	11.4	30	10,250	55.35	20
1757790	AAS130209000	51	13	20	9,000	36.72	40
1757791	AAS130309000	51	13	30	9,000	55.08	20
1757792	AAS154207500	61	15.4	20	7,500	36.6	40
1757793	AAS154307500	61	15.4	30	7,500	54.9	20
1757794	AAS173207000	68	17.3	20	7,000	37.52	40
1757795	AAS173307000	68	17.3	30	7,000	56.28	20

